




FAG

N205-E-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing N2...M1, with cage, single row, non-locating bearing, 0 ribs on outer ring, 2 rib on inner ring, type N2

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                    |
|---------------------------|--------------|------------------------------------|
| Cage                      | M1           | Two Piece Brass Cage Roller Guided |
| Tolerance class           | PN           | Normal (ISO 492:2023)              |
| Change mark               | E            | Increased Capacity Design          |
| Radial internal clearance | CN (Group N) | Normal internal clearance          |
| Number of rows            | 1            | Single-row design                  |

Main Dimensions & Performance Data

|                       |              |                                       |
|-----------------------|--------------|---------------------------------------|
| d                     | 25 mm        | Bore diameter                         |
| D                     | 52 mm        | Outside diameter                      |
| B                     | 15 mm        | Width                                 |
| C <sub>r</sub>        | 34.500 N     | Basic dynamic load rating, radial     |
| C <sub>0r</sub>       | 27.500 N     | Basic static load rating, radial      |
| C <sub>ur</sub>       | 4.400 N      | Fatigue load limit, radial            |
| n <sub>G Grease</sub> | 22.400 1/min | Limiting speed for grease lubrication |
| ≈m                    | 0,149 kg     | Masa                                  |

Mounting dimensions

|                     |        |                              |
|---------------------|--------|------------------------------|
| d <sub>a</sub>      | 29 mm  | Diameter shaft shoulder      |
| D <sub>a</sub>      | 46 mm  | Diameter of housing shoulder |
| r <sub>a1 max</sub> | 0,6 mm | Maximum recess radius        |



Dimensions

|         |         |                             |
|---------|---------|-----------------------------|
| r 1 min | 1 mm    | Minimum chamfer dimension   |
| E       | 46,5 mm | Raceway diameter outer ring |

Temperature range

|       |        |                            |
|-------|--------|----------------------------|
| T min | -30 °C | Operating temperature min. |
| T max | 150 °C | Operating temperature max. |

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia