



FAG

N218-E-XL-TVP2

Cylindrical roller bearing

Cylindrical roller bearing N2...E-TVP, with cage, single row, non-locating bearing, 0 ribs on outer ring, 2 rib on inner ring, type N2

Informacje techniczne



Twoja aktualna wersja produktu

Cage	TVP2	Solid Window Cage made from PA66
Tolerance class	PN	Normal (ISO 492:2023)
Change mark	E	Increased Capacity Design
Radial internal clearance	CN (Group N)	Normal internal clearance
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	90 mm	Bore diameter
D	160 mm	Outside diameter
B	30 mm	Width
C _r	215.000 N	Basic dynamic load rating, radial
C _{0r}	217.000 N	Basic static load rating, radial
C _{ur}	37.500 N	Fatigue load limit, radial
n _{G Grease}	5.100 1/min	Limiting speed for grease lubrication
n _{G Oil}	6.000 1/min	Limiting speed for oil lubrication
≈m	2,31 kg	Masa

Mounting dimensions

d _a	101 mm	Diameter shaft shoulder
D _a	149 mm	Diameter of housing shoulder
r _{a1 max}	2 mm	Maximum recess radius



Dimensions

r 1 min	2 mm	Minimum chamfer dimension
s 1	1,4 mm	Axial displacement
E	145 mm	Raceway diameter outer ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia