



NA4836-XL

Needle roller bearing

Needle roller bearing NA..-XL, single row,  
with inner ring, outer ring with 2 bords

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|         |          |
|---------|----------|
| Cage    | Standard |
| Coating | Without  |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 180 mm      | Bore diameter                     |
| D               | 225 mm      | Outside diameter                  |
| B               | 45 mm       | Width                             |
| C <sub>r</sub>  | 219.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 550.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 81.000 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 2.420 1/min | Limiting speed                    |
| n <sub>gr</sub> | 1.490 1/min | Reference speed                   |

Dimensions

|                  |        |                             |
|------------------|--------|-----------------------------|
| F                | 195 mm | Raceway diameter inner ring |
| r <sub>min</sub> | 1,1 mm | Minimum chamfer dimension   |
| s                | 1,5 mm | Axial displacement          |



### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Mała przestrzeń zabudowy