


**NA4924-XL-C3**

Radial roller bearing

Radial roller bearing NA..-XL


X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	Standard	
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Lubrication hole	the aid of the bearing frequency calculator, you can determine this by inputting the geometrical data.	With
Coating	Without	
Type of Seal	Without	
Special features	Without	
Number of rows	1	Single-row design



Main Dimensions & Performance Data

d	120 mm	Bore diameter
D	165 mm	Outside diameter
B	45 mm	Width
C _r	205.000 N	Basic dynamic load rating, radial
C _{0r}	390.000 N	Basic static load rating, radial
C _{ur}	65.000 N	Fatigue load limit, radial
n _G	3.400 1/min	Limiting speed
n _G Grease	2.040 1/min	Limiting speed for grease lubrication
n _{gr}	2.160 1/min	Reference speed
m	2,863 kg	Masa

Dimensions

r _{min}	1,1 mm	Minimum chamfer dimension
F	135 mm	Raceway diameter inner ring
s	2 mm	Axial displacement

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Mala przestrzeń zabudowy