

**NA6915-ZW-XL** [🔗](#)

Needle roller bearing

Needle roller bearings NA69...ZW, Dimension series 69, double row

**X-life**

## Informacje techniczne

## Twoja aktualna wersja produktu

|                  |          |                   |
|------------------|----------|-------------------|
| Cage             | Standard |                   |
| Cage feature     | Standard |                   |
| Special features | Standard |                   |
| Number of rows   | ZW       | Double-row design |

## Main Dimensions &amp; Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 75 mm       | Bore diameter                     |
| D               | 105 mm      | Outside diameter                  |
| B               | 54 mm       | Width                             |
| C <sub>r</sub>  | 147.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 275.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 50.000 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 5.400 1/min | Limiting speed                    |
| n <sub>gr</sub> | 3.150 1/min | Reference speed                   |
| ≈m              | 1,41 kg     | Masa                              |

## Dimensions

|                  |       |                             |
|------------------|-------|-----------------------------|
| F                | 85 mm | Raceway diameter inner ring |
| r <sub>min</sub> | 1 mm  | Minimum chamfer dimension   |
| s                | 1 mm  | Axial displacement          |



### Temperature range

|           |        |                            |
|-----------|--------|----------------------------|
| $T_{min}$ | -30 °C | Operating temperature min. |
| $T_{max}$ | 120 °C | Operating temperature max. |

### Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy