
**NATV25** **Yoke type track roller**

Yoke type track rollers NATV..., single row needle roller bearings with particularly thick-walled outer ring, full complement needle roller set and an inner ring, axial guidance of outer ring is provided by the contact washers, gap seals on both sides

Informacje techniczne**Twoja aktualna wersja produktu**

Sealing	SPSP	Gap seal on both sides
Outer ring profile	R500	R500

Main Dimensions & Performance Data

d	25 mm	Bore diameter
D	52 mm	Outside diameter
B	25 mm	Width of the bearing
C _{r w}	20.100 N	Basic dynamic load rating, radial
C _{0r w}	44.500 N	Basic static load rating, radial
C _{ur w}	6.300 N	Fatigue load limit, radial
n _{D G}	1.000 1/min	Speed on permanent grease lubrication
F _{0r per}	44.500 N	Permissible static load, radial
F _{r per}	43.500 N	Permissible dynamic load outer ring, radial
≈m	294,13 g	Masa

Dimensions

C	24 mm	Width, outer ring
d ₂	41,5 mm	Outside diameter of thrust washer
r _{min}	1 mm	Minimum chamfer dimension
R	500 mm	Radius of outer ring outside profile



Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia