

NATV35-PP

Yoke type track roller

Yoke type track rollers NATV..-PP-A, single row needle roller bearings with particularly thick-walled outer ring, full complement needle roller set and an inner ring, axial guidance of outer ring is provided by the plastic axial plain washers and contact washers, three-stage sealing by plastic axial plain washer on both sides

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	PP	Three-stage sealing by plastic axial plain washer on both sides
Outer ring profile	IOP	Optimized INA-profile
Relubrication feature	IR	Via inner ring

Main Dimensions & Performance Data

d	35 mm	Bore diameter
D	72 mm	Outside diameter
B	29 mm	Width of the bearing
$C_{r\,w}$	32.000 N	Basic dynamic load rating, radial
$C_{0r\,w}$	72.000 N	Basic static load rating, radial
$C_{ur\,w}$	10.300 N	Fatigue load limit, radial
$n_{D\,G}$	750 1/min	Speed on permanent grease lubrication
$F_{0r\,per}$	72.000 N	Permissible static load, radial
$F_{r\,per}$	62.000 N	Permissible dynamic load outer ring, radial
≈m	0,636 kg	Masa

Dimensions

C	28 mm	Width, outer ring
d_2	58 mm	Outside diameter of thrust washer
r_{min}	1,1 mm	Minimum chamfer dimension

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Właściwości

- Obciążenie promieniowe
- Smarowanie dożywotnie, bezobsługowe
- Smarowanie smarem
- Uszczelnienie dwustronne

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje