



FAG

NJ1076-M1 [🔗](#)

Cylindrical roller bearing

Cylindrical roller bearing NJ..-M1, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

Informacje techniczne

Twoja aktualna wersja produktu

Design	Standard	
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	380 mm	Bore diameter
D	560 mm	Outside diameter
B	82 mm	Width
C _r	1.170.000 N	Basic dynamic load rating, radial
C _{0r}	1.990.000 N	Basic static load rating, radial
C _{ur}	203.000 N	Fatigue load limit, radial
n _G	1.880 1/min	Limiting speed
n _{gr}	1.050 1/min	Reference speed
≈m	69,3 kg	Masa



Mounting dimensions

d _{a min}	397 mm	Minimum diameter shaft shoulder
d _{a max}	420 mm	Maximum diameter of shaft shoulder
D _{a max}	543 mm	Maximum diameter of housing shoulder
d _{c min}	447 mm	Minimum shaft shoulder
r _{a max}	4 mm	Maximum recess radius

Dimensions

r _{min}	5 mm	Minimum chamfer dimension
r _{1 min}	5 mm	Minimum chamfer dimension
s	9 mm	Axial displacement
E	515 mm	Raceway diameter outer ring
F	425 mm	Raceway diameter inner ring
D _{1 min}	497 mm	Minimum rib diameter outer ring
d ₁	443 mm	Maximum rib diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia