



FAG




NJ214-E-XL-TVP2

Cylindrical roller bearing

Cylindrical roller bearing NJ...E-XL-TVP2, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne




Twoja aktualna wersja produktu

|                           |              |                                  |
|---------------------------|--------------|----------------------------------|
| Design                    | E            | Increased Capacity Design        |
| Cage                      | TVP2         | Solid Window Cage made from PA66 |
| Radial internal clearance | CN (Group N) | Normal internal clearance        |
| Tolerance class           | PN           | Normal (ISO 492:2023)            |
| Number of rows            | 1            | Single-row design                |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 70 mm       | Bore diameter                     |
| D               | 125 mm      | Outside diameter                  |
| B               | 24 mm       | Width                             |
| C <sub>r</sub>  | 141.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 138.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 24.500 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 7.800 1/min | Limiting speed                    |
| n <sub>gr</sub> | 4.650 1/min | Reference speed                   |
| ≈m              | 1,16 kg     | Masa                              |



### Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a \min}$ | 79 mm  | Minimum diameter shaft shoulder      |
| $d_{a \max}$ | 82 mm  | Maximum diameter of shaft shoulder   |
| $D_{a \max}$ | 116 mm | Maximum diameter of housing shoulder |
| $d_{c \min}$ | 92 mm  | Minimum shaft shoulder               |
| $r_{a \max}$ | 1,5 mm | Maximum recess radius                |

### Dimensions

|              |          |                                 |
|--------------|----------|---------------------------------|
| $r_{\min}$   | 1,5 mm   | Minimum chamfer dimension       |
| $r_{1 \min}$ | 1,5 mm   | Minimum chamfer dimension       |
| s            | 1,2 mm   | Axial displacement              |
| E            | 113,5 mm | Raceway diameter outer ring     |
| F            | 83,5 mm  | Raceway diameter inner ring     |
| $D_{1 \min}$ | 109,4 mm | Minimum rib diameter outer ring |
| $d_1$        | 89,4 mm  | Maximum rib diameter inner ring |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Additional information

HJ214-E

L-washer

### Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia