



FAG




NJ2209-E-XL-TVP2

Cylindrical roller bearing

Cylindrical roller bearing NJ...E-XL-TVP2, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne




Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	TVP2	Solid Window Cage made from PA66
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	45 mm	Bore diameter
D	85 mm	Outside diameter
B	23 mm	Width
C _r	87.000 N	Basic dynamic load rating, radial
C _{0r}	82.000 N	Basic static load rating, radial
C _{ur}	14.100 N	Fatigue load limit, radial
n _G	11.800 1/min	Limiting speed
n _{gr}	5.800 1/min	Reference speed
≈m	0,416 kg	Masa



Mounting dimensions

d a min	52 mm	Minimum diameter shaft shoulder
d a max	54 mm	Maximum diameter of shaft shoulder
D a max	78 mm	Maximum diameter of housing shoulder
d c min	61 mm	Minimum shaft shoulder
r a max	1 mm	Maximum recess radius

Dimensions

r min	1,1 mm	Minimum chamfer dimension
r 1 min	1,1 mm	Minimum chamfer dimension
s	1,5 mm	Axial displacement
E	76,5 mm	Raceway diameter outer ring
F	54,5 mm	Raceway diameter inner ring
D 1 min	73,3 mm	Minimum rib diameter outer ring
d 1	59 mm	Maximum rib diameter inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Additional information

HJ2209-E	L-washer
----------	----------

Właściwości

- Obciążenie promieniowe
- Obciążenie osiowe jednokierunkowe
- Smarowanie smarem
- Smarowanie olejem
- Bez uszczelnienia