



FAG

NJ2216-E-XL-TVP2

Cylindrical roller bearing

Cylindrical roller bearing NJ...E-XL-TVP2,
with cage, single row, semi-locating bearing,
2 ribs on outer ring, 1 rib on inner ring, type
NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	TVP2	Solid Window Cage made from PA66
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	80 mm	Bore diameter
D	140 mm	Outside diameter
B	33 mm	Width
C _r	221.000 N	Basic dynamic load rating, radial
C _{0r}	244.000 N	Basic static load rating, radial
C _{ur}	44.000 N	Fatigue load limit, radial
n _G	7.000 1/min	Limiting speed
n _{gr}	3.400 1/min	Reference speed
≈m	2,195 kg	Masa



Mounting dimensions

d a min	91 mm	Minimum diameter shaft shoulder
d a max	94 mm	Maximum diameter of shaft shoulder
D a max	129 mm	Maximum diameter of housing shoulder
d c min	104 mm	Minimum shaft shoulder
r a max	2 mm	Maximum recess radius

Dimensions

r min	2 mm	Minimum chamfer dimension
r 1 min	2 mm	Minimum chamfer dimension
s	1,3 mm	Axial displacement
E	127,3 mm	Raceway diameter outer ring
F	95,3 mm	Raceway diameter inner ring
D 1 min	122,9 mm	Minimum rib diameter outer ring
d 1	101,5 mm	Maximum rib diameter inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Additional information

HJ216-E	L-washer
---------	----------

Właściwości

- Obciążenie promieniowe
- Obciążenie osiowe jednokierunkowe
- Smarowanie smarem
- Smarowanie olejem
- Bez uszczelnienia