



FAG




NJ222-E-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-M1, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne




Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	110 mm	Bore diameter
D	200 mm	Outside diameter
B	38 mm	Width
C _r	345.000 N	Basic dynamic load rating, radial
C _{0r}	365.000 N	Basic static load rating, radial
C _{ur}	60.000 N	Fatigue load limit, radial
n _G	6.100 1/min	Limiting speed
n _{gr}	3.250 1/min	Reference speed
≈m	5,5 kg	Masa



Mounting dimensions

d _a min	122 mm	Minimum diameter shaft shoulder
d _a max	130 mm	Maximum diameter of shaft shoulder
D _a max	188 mm	Maximum diameter of housing shoulder
d _c min	144 mm	Minimum shaft shoulder

r_a max 2,1 mm Maximum recess radius

Dimensions

r _{min}	2,1 mm	Minimum chamfer dimension
r _{1 min}	2,1 mm	Minimum chamfer dimension
s	1,5 mm	Axial displacement
E	180,5 mm	Raceway diameter outer ring
F	132,5 mm	Raceway diameter inner ring
D _{1 min}	173,82 mm	Minimum rib diameter outer ring
d ₁	141,55 mm	Maximum rib diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Additional information

HJ222-E L-washer

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia