



FAG


NJ2311-E-XL-MPAX-C3

Cylindrical roller bearing

Cylindrical roller bearing NJ...E-XL-MPAX, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	MPAX	One Piece Brass Cage Lip Guided
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	55 mm	Bore diameter
D	120 mm	Outside diameter
B	43 mm	Width
C _r	235.000 N	Basic dynamic load rating, radial
C _{0r}	230.000 N	Basic static load rating, radial
C _{ur}	44.000 N	Fatigue load limit, radial
n _G	10.400 1/min	Limiting speed
n _{gr}	4.500 1/min	Reference speed
≈m	2,48 kg	Masa



Mounting dimensions

$d_{a \min}$	66 mm	Minimum diameter shaft shoulder
$d_{a \max}$	69 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	109 mm	Maximum diameter of housing shoulder
$d_{c \min}$	80 mm	Minimum shaft shoulder

Dimensions

$r_{\min}$	2 mm	Minimum chamfer dimension
$r_{1 \min}$	2 mm	Minimum chamfer dimension
s	3,3 mm	Axial displacement
E	106,5 mm	Raceway diameter outer ring
F	70,5 mm	Raceway diameter inner ring
$D_{1 \min}$	101,42 mm	Minimum rib diameter outer ring
d_1	77,5 mm	Maximum rib diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

Additional information

HJ2311-E

L-washer

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia