



FAG


NJ2313-E-XL-MPAX-C4

Cylindrical roller bearing

Cylindrical roller bearing NJ...-E-XL-MPAX, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | E            | Increased Capacity Design         |
| Cage                      | MPAX         | One Piece Brass Cage Lip Guided   |
| Radial internal clearance | C4 (Group 4) | Internal clearance larger than C3 |
| Tolerance class           | PN           | Normal (ISO 492:2023)             |
| Number of rows            | 1            | Single-row design                 |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 65 mm       | Bore diameter                     |
| D               | 140 mm      | Outside diameter                  |
| B               | 48 mm       | Width                             |
| C <sub>r</sub>  | 295.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 285.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 54.000 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 8.800 1/min | Limiting speed                    |
| n <sub>gr</sub> | 4.000 1/min | Reference speed                   |
| m               | 3,7 kg      | Masa                              |



Mounting dimensions

|                    |        |                                      |
|--------------------|--------|--------------------------------------|
| d <sub>a min</sub> | 77 mm  | Minimum diameter shaft shoulder      |
| d <sub>a max</sub> | 81 mm  | Maximum diameter of shaft shoulder   |
| D <sub>a max</sub> | 128 mm | Maximum diameter of housing shoulder |
| d <sub>c min</sub> | 93 mm  | Minimum shaft shoulder               |
| r <sub>a max</sub> | 2 mm   | Maximum recess radius                |

Dimensions

|                    |           |                                 |
|--------------------|-----------|---------------------------------|
| r <sub>min</sub>   | 2,1 mm    | Minimum chamfer dimension       |
| r <sub>1 min</sub> | 2,1 mm    | Minimum chamfer dimension       |
| s                  | 4 mm      | Axial displacement              |
| E                  | 124,5 mm  | Raceway diameter outer ring     |
| F                  | 82,5 mm   | Raceway diameter inner ring     |
| D <sub>1 min</sub> | 118,56 mm | Minimum rib diameter outer ring |
| d <sub>1</sub>     | 90,5 mm   | Maximum rib diameter inner ring |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 150 °C | Operating temperature max. |

Additional information

|          |          |
|----------|----------|
| HJ2313-E | L-washer |
|----------|----------|

Właściwości

|  |                                   |
|--|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |