



FAG

NJ2324-E-XL-M1-C4

Cylindrical roller bearing

Cylindrical roller bearing NJ...-E-XL-M1, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	120 mm	Bore diameter
D	260 mm	Outside diameter
B	86 mm	Width
C _r	930.000 N	Basic dynamic load rating, radial
C _{0r}	1.010.000 N	Basic static load rating, radial
C _{ur}	169.000 N	Fatigue load limit, radial
n _G	4.550 1/min	Limiting speed
n _{gr}	1.980 1/min	Reference speed
≈m	23,8 kg	Masa



Mounting dimensions

d _a min	134 mm	Minimum diameter shaft shoulder
d _a max	151 mm	Maximum diameter of shaft shoulder
D _a max	246 mm	Maximum diameter of housing shoulder
d _c min	171 mm	Minimum shaft shoulder

r_a max 2,5 mm Maximum recess radius

Dimensions

r _{min}	3 mm	Minimum chamfer dimension
r ₁ min	3 mm	Minimum chamfer dimension
s	7,2 mm	Axial displacement
E	230 mm	Raceway diameter outer ring
F	154 mm	Raceway diameter inner ring
D ₁ min	218,7 mm	Minimum rib diameter outer ring
d ₁	168,1 mm	Maximum rib diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Additional information

HJ2324-E L-washer

Właściwości

- Obciążenie promieniowe
- Obciążenie osiowe jednokierunkowe
- Smarowanie smarem
- Smarowanie olejem
- Bez uszczelnienia