



FAG

NJ2336-EX-TB-XL-MPAX-ILR-J30PC

Cylindrical roller bearing

Cylindrical roller bearing NJ...-E...-MPAX-ILR, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	MPAX	One Piece Brass Cage Lip Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	180 mm	Bore diameter
D	380 mm	Outside diameter
B	126 mm	Width
C _r	2.460.000 N	Basic dynamic load rating, radial
C _{0r}	2.330.000 N	Basic static load rating, radial
C _{ur}	320.000 N	Fatigue load limit, radial
n _G	3.000 1/min	Limiting speed
n _{gr}	1.120 1/min	Reference speed
≈m	72,1 kg	Masa

Mounting dimensions

D _{a max}	363 mm	Maximum diameter of housing shoulder
--------------------	--------	--------------------------------------



Dimensions

r _{min}	4 mm	Minimum chamfer dimension
r _{1 min}	4 mm	Minimum chamfer dimension
s	10,5 mm	Axial displacement
E	339 mm	Raceway diameter outer ring
F	227 mm	Raceway diameter inner ring
D _{1 min}	316,6 mm	Minimum rib diameter outer ring
d ₁	249,4 mm	Maximum rib diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Smarowanie smarem
- 

Smarowanie olejem
- 

Bez uszczelnienia
- 

Łożysko gabarytowe