



FAG


NJ318-E-XL-MPAX-J30PC-C3 [🔗](#)

Cylindrical roller bearing

Cylindrical roller bearing NJ...-E-XL-MPAX, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | E            | Increased Capacity Design         |
| Cage                      | MPAX         | One Piece Brass Cage Lip Guided   |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Tolerance class           | PN           | Normal (ISO 492:2023)             |
| Number of rows            | 1            | Single-row design                 |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 90 mm       | Bore diameter                     |
| D               | 190 mm      | Outside diameter                  |
| B               | 43 mm       | Width                             |
| C <sub>r</sub>  | 390.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 375.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 65.000 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 6.300 1/min | Limiting speed                    |
| n <sub>gr</sub> | 3.550 1/min | Reference speed                   |
| ≈m              | 6,055 kg    | Masa                              |



Mounting dimensions

|                    |        |                                      |
|--------------------|--------|--------------------------------------|
| d <sub>a min</sub> | 104 mm | Minimum diameter shaft shoulder      |
| d <sub>a max</sub> | 111 mm | Maximum diameter of shaft shoulder   |
| D <sub>a max</sub> | 176 mm | Maximum diameter of housing shoulder |
| d <sub>c min</sub> | 127 mm | Minimum shaft shoulder               |

|                    |        |                       |
|--------------------|--------|-----------------------|
| r <sub>a max</sub> | 2,5 mm | Maximum recess radius |
|--------------------|--------|-----------------------|

Dimensions

|                    |           |                                 |
|--------------------|-----------|---------------------------------|
| r <sub>min</sub>   | 3 mm      | Minimum chamfer dimension       |
| r <sub>1 min</sub> | 3 mm      | Minimum chamfer dimension       |
| s                  | 1,5 mm    | Axial displacement              |
| E                  | 169,5 mm  | Raceway diameter outer ring     |
| F                  | 113,5 mm  | Raceway diameter inner ring     |
| D <sub>1 min</sub> | 161,62 mm | Minimum rib diameter outer ring |
| d <sub>1</sub>     | 124 mm    | Maximum rib diameter inner ring |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 150 °C | Operating temperature max. |

Additional information

HJ318-E L-washer

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia