
**NK60/25-F-XL**

Needle roller bearing

Needle roller bearing NK...F-XL, single row,
no inner ring, outer ring with 2 bords**X-life**

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	Without	
Cage	F	Cage of steel
Cage feature	Standard	
Tolerance class	PN	Normal (DIN 620-2)

Main Dimensions & Performance Data

F_w	60 mm	Under roller diameter
D	72 mm	Outside diameter
C	25 mm	Width, outer ring
C_r	47.500 N	Basic dynamic load rating, radial
C_{0r}	90.000 N	Basic static load rating, radial
C_{ur}	15.600 N	Fatigue load limit, radial
n_G	7.700 1/min	Limiting speed
n_{gr}	4.800 1/min	Reference speed
$\approx m$	184,6 g	Masa

Dimensions

r_{min}	0,6 mm	Minimum chamfer dimension
-----------	--------	---------------------------



Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy