



NKI42/30-IS1-XL-C3

Needle roller bearing

Needle roller bearings NKI, light series

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	Standard	
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (DIN 620-2)
Lubrication hole	IS1	IS1
Coating	Without	
Lubricant	Without	

Main Dimensions & Performance Data

d	42 mm	Bore diameter
D	57 mm	Outside diameter
B	30 mm	Width
C _r	48.500 N	Basic dynamic load rating, radial
C _{0r}	94.000 N	Basic static load rating, radial
C _{ur}	17.800 N	Fatigue load limit, radial
n _G	9.800 1/min	Limiting speed
n _{gr}	5.400 1/min	Reference speed
≈m	221,7 g	Masa



Dimensions

F	47 mm	Raceway diameter inner ring
r _{min}	0,3 mm	Minimum chamfer dimension
s	1 mm	Axial displacement

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Mała przestrzeń zabudowy