NKIA5914-XL

Needle roller/angular contact ball bearing

Informacje techniczne



Main Dimensions & Performance Data

d	70 mm	Bore diameter
D	100 mm	Outside diameter
B	40 mm	Width
C_r	95.000 N	Basic dynamic load rating, radial
C_{0r}	156.000 N	Basic static load rating, radial
C_a	16.800 N	Basic dynamic load rating, axial
C_{0a}	44.500 N	Basic static load rating, axial
C_{ur}	28.000 N	Fatigue limit load, radial
C_{ur}	28.000 N	Fatigue load limit, radial
C_{ua}	2.020 N	Fatigue load limit, axial
n_G	5.800 1/min	Limiting speed
$n_{\vartheta r}$	4.900 1/min	Reference speed
≈m	968,13 g	Masa

Dimensions

F	80 mm	Raceway diameter inner ring
r_{min}	1 mm	Minimum chamfer dimension

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Właściwości

Obciążenie promieniowe

Obciążenie osiowe jednokierunkowe

Smarowanie smarem

Smarowanie olejem

Bez uszczelnienia

Mała przestrzeń zabudowy

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje