


NKIB59/22-XL

Needle roller/angular contact ball bearing

Needle roller/angular contact ball bearings
NKIB, double direction axial component

X-life

Informacje techniczne



Main Dimensions & Performance Data

d	22 mm	Bore diameter
D	39 mm	Outside diameter
B	25 mm	Width
C _r	26.000 N	Basic dynamic load rating, radial
C _{0r}	29.500 N	Basic static load rating, radial
C _a	5.300 N	Basic dynamic load rating, axial
C _{0a}	8.600 N	Basic static load rating, axial
C _{ur}	5.400 N	Fatigue load limit, radial
C _{ua}	395 N	Fatigue load limit, axial
n _G	16.100 1/min	Limiting speed
n _{gr}	12.000 1/min	Reference speed
≈m	115,01 g	Masa

Dimensions

F	28 mm	Raceway diameter inner ring
C	23 mm	Width, outer ring
r _{min}	0,3 mm	Minimum chamfer dimension



Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy