



NKX70-Z-XL

Needle roller/axial ball bearing

Needle roller/axial ball bearings NKX...Z, axial component, single direction, to DIN 5429, with end cap, for grease lubrication

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Type of Seal	Z	Bearing with end cap
Cage	Standard	

Main Dimensions & Performance Data

F_w	70 mm	Bore diameter
D	85 mm	Outside diameter
C	40 mm	Height
C_r	50.000 N	Basic dynamic load rating, radial
C_{0r}	92.000 N	Basic static load rating, radial
C_a	43.000 N	Basic dynamic load rating, axial
C_{0a}	127.000 N	Basic static load rating, axial
C_{ur}	16.000 N	Fatigue load limit, radial
C_{ua}	6.300 N	Fatigue load limit, axial
n_G	2.400 1/min	Limiting speed
$\approx m$	583,84 g	Masa

Mounting dimensions

d_a	90,5 mm	Mounting dimension shaft shoulder
$r_{a\max}$	1 mm	Maximum recess radius



Dimensions

D 1 max	96,5 mm	Maximum outside diameter flange
D 2 max	96,5 mm	Maximum outside diameter flange
C 1	18 mm	Width of the axial brearing component
C 1	11 mm	Distance to lubrication hole
C 2	11 mm	Distance to lubrication hole
d w	70 mm	Bore diameter of shaft washer
r min	1 mm	Minimum chamfer dimension

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Additional information

IR60X70X25-XL	Suitable inner rings IR
---------------	-------------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Uszczelnienie jednostronne