

FAG




NN3019-D-K-TVP-SP-XL

Cylindrical roller bearing

Super precision cylindrical roller bearings
NN30...-D-K-TVP-SP, Non-locating bearing,
double row, with tapered bore, taper 1:12,
separable, with cage

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	TVP	Plastic cage
Tolerance class	SP	Tolerance class SP
Bore type	K	Tapered, taper 1:12
Change mark	D	Internal Variant D
Radial internal clearance	C1 (Group 1)	Internal clearance smaller than C2
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	95 mm	Bore diameter
D	145 mm	Outside diameter
B	37 mm	Width
C _r	170.000 N	Basic dynamic load rating, radial
C _{0r}	234.000 N	Basic static load rating, radial
C _{ur}	36.000 N	Fatigue load limit, radial
n _{G Grease}	7.300 1/min	Limiting speed for grease lubrication
n _{G Oil}	8.600 1/min	Limiting speed for oil lubrication
≈m	2,01 kg	Masa



Mounting dimensions

d_a	110 mm	Diameter shaft shoulder
h_{12}		Diameter shaft shoulder tolerance
D_a	134,8 mm	Diameter of housing shoulder
H_{12}		Shoulder diameter outer ring clearance
$E_{tk1\text{ nom}}$	129,8 mm	Injection pitch diameter min
$r_{a1\text{ max}}$	1,5 mm	Maximum recess radius

Dimensions

$r_1\text{ min}$	1,5 mm	Minimum chamfer dimension
E	132 mm	Raceway diameter outer ring
s	2,5 mm	Axial displacement

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia