


NNTR100X240X105-2ZL

Yoke type track roller

Yoke type track roller NNTR..-2ZL, CRB, full complement roller set, two-row, with inner ring, 3 ribs on outer ring, not pallet changer

Informacje techniczne



Twoja aktualna wersja produktu

Type of Seal	2ZL	Sealing shields on both sides
--------------	-----	-------------------------------

Main Dimensions & Performance Data

d	100 mm	Bore diameter
D	240 mm	Outside diameter
B	105 mm	Width, inner ring
C _{r w}	550.000 N	Basic dynamic load rating, radial
C _{0r w}	880.000 N	Basic static load rating, radial
C _{ur w}	126.000 N	Fatigue load limit, radial
n _{D G}	340 1/min	Speed on permanent grease lubrication
F _{0r per}	880.000 N	Permissible static load, radial
F _{r per}	710.000 N	Permissible dynamic load outer ring, radial
≈m	27,15 kg	Masa

Mounting dimensions

d ₂	132 mm	Stop diameter of thrust washer
D ₁	160 mm	Mounting dimension
d ₃	6 mm	Diameter lubrication hole
R	10.000 mm	Radius of outer ring outside profile
	6	Number of lubrication holes



Dimensions

C	103 mm	Width, outer ring
r min	4 mm	Minimum chamfer dimension
r 1 min	2,5 mm	Minimum chamfer dimension

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Obciążenie osiowe dwukierunkowe
- 

Smarowanie dożywotnie, bezobsługowe
- 

Smarowanie smarem
- 

Uszczelnienie dwustronne