


NNTR70X180X85-2ZL

Yoke type track roller

Yoke type track roller NNTR..-2ZL, CRB, full complement roller set, two-row, with inner ring, 3 ribs on outer ring, not pallet changer

Informacje techniczne



Twoja aktualna wersja produktu

Type of Seal	2ZL	Sealing shields on both sides
--------------	-----	-------------------------------

Main Dimensions & Performance Data

d	70 mm	Bore diameter
D	180 mm	Outside diameter
B	85 mm	Width, inner ring
C _{r w}	350.000 N	Basic dynamic load rating, radial
C _{0r w}	520.000 N	Basic static load rating, radial
C _{ur w}	80.000 N	Fatigue load limit, radial
n _{D G}	600 1/min	Speed on permanent grease lubrication
F _{0r per}	520.000 N	Permissible static load, radial
F _{r per}	465.000 N	Permissible dynamic load outer ring, radial
≈m	12,8 kg	Masa

Mounting dimensions

d ₂	92 mm	Stop diameter of thrust washer
D ₁	115 mm	Mounting dimension
d ₃	5 mm	Diameter lubrication hole
R	10.000 mm	Radius of outer ring outside profile
	3	Number of lubrication holes



Dimensions

C	83 mm	Width, outer ring
r min	3 mm	Minimum chamfer dimension
r 1 min	2 mm	Minimum chamfer dimension

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne