



FAG




NU202-E-XL-TVP2

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-XL-TVP2, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	TVP2	Solid Window Cage made from PA66
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	15 mm	Bore diameter
D	35 mm	Outside diameter
B	11 mm	Width
C _r	15.100 N	Basic dynamic load rating, radial
C _{0r}	10.400 N	Basic static load rating, radial
C _{ur}	1.440 N	Fatigue load limit, radial
n _G	31.000 1/min	Limiting speed
n _{gr}	17.900 1/min	Reference speed
m	0,047 kg	Masa



Mounting dimensions

$d_{a\ min}$	17,4 mm	Minimum diameter shaft shoulder
$d_{a\ max}$	18,5 mm	Maximum diameter of shaft shoulder
$d_{b\ min}$	20 mm	Minimum shaft shoulder
$D_{a\ max}$	32,6 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	0,6 mm	Maximum recess radius
$r_{a1\ max}$	0,3 mm	Maximum recess radius

Dimensions

$r_{\min}$	0,6 mm	Minimum chamfer dimension
$r_{1\ min}$	0,3 mm	Minimum chamfer dimension
s	1,6 mm	Axial displacement
E	30,3 mm	Raceway diameter outer ring
F	19,3 mm	Raceway diameter inner ring
$D_{1\ min}$	28 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia