



FAG

NU2276-E-M1A

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-M1A, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

Informacje techniczne

Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1A	Two Piece Brass Cage Lip guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	380 mm	Bore diameter
D	680 mm	Outside diameter
B	175 mm	Width
C _r	4.050.000 N	Basic dynamic load rating, radial
C _{0r}	6.700.000 N	Basic static load rating, radial
C _{ur}	620.000 N	Fatigue load limit, radial
n _G	1.420 1/min	Limiting speed
n _{gr}	450 1/min	Reference speed
≈m	286,02 kg	Masa



Mounting dimensions

$d_{a \min}$	406 mm	Minimum diameter shaft shoulder
$d_{a \max}$	446 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	456 mm	Minimum shaft shoulder
$D_{a \max}$	654 mm	Maximum diameter of housing shoulder
$r_{a \max}$	5 mm	Maximum recess radius
$r_{a1 \max}$	5 mm	Maximum recess radius

Dimensions

$r_{\min}$	6 mm	Minimum chamfer dimension
$r_{1 \min}$	6 mm	Minimum chamfer dimension
s	13,8 mm	Axial displacement
E	615 mm	Raceway diameter outer ring
F	451 mm	Raceway diameter inner ring
$D_{1 \min}$	582,2 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia