



FAG

NU330-E-XL-MCA-C3

Cylindrical roller bearing

Cylindrical roller bearing NU20..-E-XL-MCA, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

Informacje techniczne

Twoja aktualna wersja produktu

Design	Standard	
Cage	MCA	Messing Käfig, einteilig, bordgeführt am Außenring
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	320 mm	Outside diameter
B	65 mm	Width
C _r	900.000 N	Basic dynamic load rating, radial
C _{0r}	930.000 N	Basic static load rating, radial
C _{ur}	108.000 N	Fatigue load limit, radial
n _G	3.650 1/min	Limiting speed
n _{gr}	1.940 1/min	Reference speed
m	26,4 kg	Masa



Mounting dimensions

$d_{a \min}$	167 mm	Minimum diameter shaft shoulder
$d_{a \max}$	190 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	195 mm	Minimum shaft shoulder
$D_{a \max}$	303 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum recess radius
$r_{a1 \max}$	3 mm	Maximum recess radius

Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
$r_{1 \min}$	4 mm	Minimum chamfer dimension
s	5,5 mm	Axial displacement
E	283 mm	Raceway diameter outer ring
F	193 mm	Raceway diameter inner ring
$D_{1 \min}$	269,8 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia