






FAG

NUP238-E-M1

Cylindrical roller bearing

Cylindrical roller bearing NUP...-E-M1, with cage, single row, locating bearing, 2 ribs on outer ring, 1 rib on inner ring, rib washer internal, type NUP

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	190 mm	Bore diameter
D	340 mm	Outside diameter
B	55 mm	Width
C _r	680.000 N	Basic dynamic load rating, radial
C _{0r}	930.000 N	Basic static load rating, radial
C _{ur}	112.000 N	Fatigue load limit, radial
n _G	3.050 1/min	Limiting speed
n _{gr}	1.720 1/min	Reference speed
≈m	21,4 kg	Masa



Mounting dimensions

d_1	244 mm	Maximum rib diameter inner ring
$D_1 \text{ min}$	295 mm	Minimum rib diameter outer ring
$d_a \text{ min}$	207 mm	Minimum diameter shaft shoulder
$d_c \text{ min}$	247 mm	Minimum shaft shoulder
$D_a \text{ max}$	323 mm	Maximum diameter of housing shoulder
$r_a \text{ max}$	3 mm	Maximum recess radius

Dimensions

r_{min}	4 mm	Minimum chamfer dimension
$r_1 \text{ min}$	4 mm	Minimum chamfer dimension
E	306 mm	Raceway diameter outer ring
F	230 mm	Raceway diameter inner ring
B_3	8,5 mm	Width of loose rib

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe