


NX20-Z-XL

Needle roller/axial ball bearing

Needle roller/axial ball bearings NX...-Z,
single direction axial component, for grease
lubrication

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Type of Seal Z Bearing with end cap

Cage Standard

Main Dimensions & Performance Data

F _w	20 mm	Bore diameter
D	30 mm	Outside diameter
C	28 mm	Height
C _r	14.600 N	Basic dynamic load rating, radial
C _{0r}	17.500 N	Basic static load rating, radial
C _a	7.000 N	Basic dynamic load rating, axial
C _{0a}	14.700 N	Basic static load rating, axial
C _{ur}	3.300 N	Fatigue load limit, radial
C _{ua}	670 N	Fatigue load limit, axial
n _G	6.500 1/min	Limiting speed
≈m	67,17 g	Masa



Mounting dimensions

d_a	25 mm	Mounting dimension shaft shoulder
$r_{a \max}$	0,3 mm	Maximum recess radius
D_1	33,6 mm	Connection diameter snap ring
C_2	12,2 mm	Connection width with snap ring

Dimensions

C_1	8 mm	Distance to lubrication hole
C_2	8 mm	Distance to lubrication hole
d_w	20 mm	Bore diameter of shaft washer
$r_{\min}$	0,3 mm	Minimum chamfer dimension

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Additional information

IR17X20X16-XL	Suitable inner rings IR
WR30, SW30	Snap ring

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Uszczelnienie jednostronne