


NX30-Z-XL

Needle roller/axial ball bearing

Needle roller/axial ball bearings NX...-Z,
single direction axial component, for grease
lubrication

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Type of Seal Z Bearing with end cap

Cage Standard

Main Dimensions & Performance Data

F _w	30 mm	Bore diameter
D	42 mm	Outside diameter
C	30 mm	Height
C _r	25.500 N	Basic dynamic load rating, radial
C _{0r}	36.000 N	Basic static load rating, radial
C _a	11.700 N	Basic dynamic load rating, axial
C _{0a}	28.000 N	Basic static load rating, axial
C _{ur}	6.400 N	Fatigue load limit, radial
C _{ua}	1.270 N	Fatigue load limit, axial
n _G	4.300 1/min	Limiting speed
≈m	121,25 g	Masa



Mounting dimensions

d_a	36,5 mm	Mounting dimension shaft shoulder
$r_{a \max}$	0,3 mm	Maximum recess radius
D_1	45,1 mm	Connection diameter snap ring
C_2	14,2 mm	Connection width with snap ring

Dimensions

C_1	10 mm	Distance to lubrication hole
C_2	10 mm	Distance to lubrication hole
d_w	30 mm	Bore diameter of shaft washer
$r_{\min}$	0,3 mm	Minimum chamfer dimension

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Additional information

IR25X30X20-XL	Suitable inner rings IR
WR42, SW42	Snap ring

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Uszczelnienie jednostronne