


**OCE35-DC-B-VA-FD**

Radial insert ball bearing

Informacje techniczne

**Main Dimensions & Performance Data**

d	35 mm	Bore diameter
D _{SP}	72 mm	Outside diameter
C _{0r}	12.500 N	Basic static load rating, radial
C _{ur}	1.000 N	Fatigue load limit, radial
B ₁	44,5 mm	Locking collar total width
C _r	21.900 N	Basic dynamic load rating, radial
≈m	0,51 kg	Masa

Dimensions

C	20 mm	Width, outer ring
C ₂	24 mm	Sealing total width
S	17,5 mm	Distance raceway
d ₁	47,45 mm	Rib diameter inner ring
d ₃	57 mm	Outside diameter locking collar/locknut
W	4 mm	Width of flats

Temperature range

T _{min}	-35 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.



Calculation factors

f_0	13,9	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	L _h Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne
	Ochrona przed korozją
	Nieosiowość statyczna