


PAGBAO50-PP-AS

Linear plain bearing and housing unit

Linear plain bearing and housing unit; open design, sealed on all sides, with relubrication facility

Informacje techniczne



Twoja aktualna wersja produktu

Size 50

Seal PP

Relubrication feature AS

Main Dimensions & Performance Data

F<sub>W</sub> 50 mm Diameter of ball complement

H 92,8 mm Height

L 100 mm Length

Tol<sub>L</sub> h12 Tolerance

B 130 mm Width

≈m 1,46 kg Masa



Mounting dimensions

|                    |          |                        |
|--------------------|----------|------------------------|
| J <sub>B</sub>     | 108 mm   |                        |
| Tol J <sub>B</sub> | + 0,2 mm | Upper tolerance        |
| Tol J <sub>B</sub> | - 0,2 mm | Lower tolerance        |
| A <sub>5</sub>     | 65 mm    |                        |
| B <sub>2</sub>     | 22,7 mm  |                        |
| L <sub>4</sub>     | 70 mm    |                        |
| L <sub>5</sub>     | 72 mm    |                        |
| J <sub>L</sub>     | 50 mm    |                        |
| Tol J <sub>L</sub> | + 0,2 mm | Upper tolerance        |
| Tol J <sub>L</sub> | - 0,2 mm | Lower tolerance        |
| H <sub>2</sub>     | 50 mm    | Center height          |
| A <sub>3</sub>     | 19 mm    |                        |
| H <sub>6</sub>     | 12,5 mm  |                        |
| Tol H <sub>6</sub> | - 0,5 mm | Tolerance              |
| N <sub>1</sub>     | 9,2 mm   | Mounting Dimension     |
| N <sub>3</sub>     | 15 mm    | Mounting Dimension     |
| K <sub>5</sub>     | M8       |                        |
| K <sub>8</sub>     | NIPA2    | Lubrication nipple     |
| W                  | 4 mm     | Width across flats     |
| M W <sub>max</sub> | 7 Nm     | Max. tightening torque |
| α                  | 54 °     | Angle                  |