



IMAGE  
COMING SOON**PCJ35-TV-FA125.5** [↗](#)

Flanged housing unit

Flanged housing unit PCJ...-TV

## Informacje techniczne



## Twoja aktualna wersja produktu

|                           |         |                                 |
|---------------------------|---------|---------------------------------|
| Material                  | TV      | Plastic                         |
| Manufacturing instruction | FA125.5 | Bearing with Corroctect coating |

## Main Dimensions &amp; Performance Data

|                   |          |                                   |
|-------------------|----------|-----------------------------------|
| d                 | 35 mm    | Bore diameter                     |
| L                 | 117 mm   | Flange width                      |
| U                 | 51 mm    | Total height unit                 |
| C <sub>r</sub>    | 22.500 N | Basic dynamic load rating, radial |
| C <sub>0r</sub>   | 12.500 N | Basic static load rating, radial  |
| C <sub>0r G</sub> | 18.500 N | Load carrying capacity (housing)  |
| ≈m                | 0,79 kg  | Masa                              |

## Mounting dimensions

|   |       |                          |
|---|-------|--------------------------|
| J | 92 mm | Distance fixing bore     |
| N | 13 mm | Fixing bore              |
| n | 4     | Number of screwing holes |



Dimensions

|                |            |                                   |
|----------------|------------|-----------------------------------|
| A              | 34,8 mm    | Height housing                    |
| A <sub>1</sub> | 15,5 mm    | Thickness of flange               |
| A <sub>2</sub> | 21,5 mm    | Distance raceway                  |
| V              | 90 mm      | Shoulder diameter housing         |
| Q              | 1/4-28 UNF | Connection thread for lubrication |
| d <sub>3</sub> | 55 mm      | Outside diameter locking device   |

Additional information

|                          |                     |
|--------------------------|---------------------|
| 1                        | Number of housings  |
| GEH.CJ07-TV-HLA          | Housing             |
| GRAE35-NPP-B-FA107/125.5 | Bearing designation |
| KASK07                   | Protecting cap      |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -35 °C | Operating temperature min. |
| T <sub>max</sub> | 100 °C | Operating temperature max. |