




PCJT30-XL-N-FA125

Flanged housing unit

Housing units PCJT...FA125, two-bolt flanged housing units, cast iron, eccentric locking collar, P seals, with anti-corrosion protection

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Groove	N	Cast iron housing with undercut slot for end caps
Material	GG	Grey cast iron
Manufacturing instruction	FA125	Unit with Corrotect coating, corrosion-resistant

Main Dimensions & Performance Data

d	30 mm	Bore diameter
L	80 mm	Flange width
H	142 mm	Height flange
U	46,8 mm	Total height unit
C _r	20.700 N	Basic dynamic load rating, radial
C _{0r}	11.300 N	Basic static load rating, radial
C _{ur}	480 N	Fatigue load limit, radial
≈m	0,84 kg	Masa

Mounting dimensions

J	116,5 mm	Distance fixing bore
N	11,5 mm	Fixing bore
n	2	Number of screwing holes
W	4 mm	Width of flats



Dimensions

A	31 mm	Height housing
A 1	12 mm	Thickness of flange
A 2	20 mm	Distance raceway
B 1	35,8 mm	Locking collar total width
V	80 mm	Shoulder diameter housing
Q	M6	Connection thread for lubrication
d 3	44 mm	Outside diameter locking collar

Additional information

1	Number of housings
GEHCJT06-N-FA125.1	Housing
GRAE30-XL-NPP-B-FA125.5	Bearing designation
KASK06	Protecting cap

Temperature range

T min	-20 °C	Operating temperature min.
T max	120 °C	Operating temperature max.