



IMAGE
COMING SOON





PCJT50-TV-FA125.5 [↗](#)

Flanged housing unit

Flanged housing unit PCJT...-TV

Informacje techniczne



Twoja aktualna wersja produktu

Material	TV	Plastic
Manufacturing instruction	FA125.5	Bearing with Corrotect coating

Main Dimensions & Performance Data

d	50 mm	Bore diameter
L	115 mm	Flange width
H	197 mm	Height flange
U	57,8 mm	Total height unit
C _r	34.000 N	Basic dynamic load rating, radial
C _{0r}	20.800 N	Basic static load rating, radial
≈m	1,179 kg	Masa

Mounting dimensions

J	157 mm	Distance fixing bore
N	17 mm	Fixing bore
n	2	Number of screwing holes



Dimensions

A	43 mm	Height housing
A ₁	21 mm	Thickness of flange
A ₂	25 mm	Distance raceway
V	115 mm	Shoulder diameter housing
Q	1/4-28 UNF	Connection thread for lubrication
d ₃	69 mm	Outside diameter locking collar

Additional information

1	Number of housings
CJT10-TV	Housing
GRAE50-NPP-B-FA107/125.5	Bearing designation
KASK10	Protecting cap

Temperature range

T _{min}	-35 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.