




PTUE45-XL

Take-up housing unit

Take-up housing units PTUE, cast iron housing, radial insert ball bearing with eccentric locking collar, P seals

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Material	GG	Grey cast iron
----------	----	----------------

Main Dimensions & Performance Data

d	45 mm	Bore diameter
---	-------	---------------

H	115 mm	Height
---	--------	--------

L	141 mm	Length total
---	--------	--------------

B 1	43,8 mm	Locking collar total width
-----	---------	----------------------------

≈m	2,32 kg	Masa
----	---------	------

Mounting dimensions

A 1	16 mm	Width guidance groove
-----	-------	-----------------------

H13		Width guidance groove clearance
-----	--	---------------------------------

H 1	102 mm	Distance guidance grooves
-----	--------	---------------------------

0,15 mm		Upper distance guidance groove tolerance
---------	--	--

-0,15 mm		Lower distance guidance groove tolerance
----------	--	--

N	29 mm	Fixing bore
---	-------	-------------



Dimensions

L 1	88 mm	Distance shaft axis
L 2	16 mm	Length fixed link
L 3	82 mm	Length guidance groove
A	50 mm	Width housing fixing side
N 1	20 mm	Width recess
N 2	49 mm	Height recess
S 1	32,8 mm	Distance of raceway to locking collar
T	82 mm	Height housing fixing side
Q	M6	Connection thread for lubrication
A 2	35 mm	Width housing

Additional information

TUE09	Housing
GRAE45-XL-NPP-B	Bearing designation

Temperature range

T min	-20 °C	Operating temperature min.
T max	120 °C	Operating temperature max.