


PWKR40-2RS-XL [↗](#)

Stud type track roller

Stud type track rollers PWKR...-2RS-XL, double row cylindrical roller bearings with particularly thick-walled outer ring, with a central rib, full complement cylindrical roller set and with a solid roller stud with fixing thread and a mounting aid, the outer ring is guided axially by the central rib and rolling elements, protected lip seal on both sides, without eccentric collar, X-life design

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Type of Seal	2RS	Protected lip seal on both sides
Outer ring profile	IOP	Optimized INA-profile
Grease nipples	2x	Drive-fit lubrication nipple unmounted 2x
Relubrication feature	KSP	Via head, stud and fit
Assembling aid head	I6	Hexagon socket
Assembling aid stud	I6	Hexagon socket

Main Dimensions & Performance Data

D	40 mm	Outside diameter
d ₁	18 mm	Fit diameter of roller stud / stud
B	58 mm	Width
C _{rw}	14.300 N	Basic dynamic load rating, radial
C _{0rw}	18.200 N	Basic static load rating, radial
C _{urw}	2.200 N	Fatigue load limit, radial
n _{DG}	5.000 1/min	Speed on permanent grease lubrication
F _{0r per}	18.200 N	Permissible static load, radial
F _{r per}	16.400 N	Permissible dynamic load outer ring, radial
≈m	236 g	Masa



Dimensions

B 1	21,6 mm	Width of thrust washer
B 2	36,5 mm	Bolt/stud length effectively
B 3	8 mm	Distance to lubrication hole
C	20 mm	Width, outer ring
C 1	0,8 mm	Protrusion outer ring to thrust washer
r min	1 mm	Minimum chamfer dimension
d 2	22 mm	Stop diameter of thrust washer
d 3	3 mm	Diameter lubrication hole
G	M18X1,5	Thread
l G	19 mm	Thread length
W	8 mm	Width of flats

Additional information

	NIPA2X7,5	Drive-fit lubrication nipple
M A	87 Nm	Tightening torque nut

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne