


PWTR20-2RS-XL

Yoke type track roller

Yoke type track rollers PWTR...-2RS-XL, double row cylindrical roller bearings with particularly thick-walled outer ring, with a central rib, full complement cylindrical roller set and an inner ring, the outer ring is guided axially by the central rib and rolling elements, protected lip seal on both sides, X-life design

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	2RS	Protected lip seal on both sides
Outer ring profile	IOP	Optimized INA-profile
Relubrication feature	IR	Via inner ring

Main Dimensions & Performance Data

d	20 mm	Bore diameter
D	47 mm	Outside diameter
B	25 mm	Width of the bearing
C _{rw}	24.400 N	Basic dynamic load rating, radial
C _{0rw}	31.000 N	Basic static load rating, radial
C _{urw}	3.800 N	Fatigue load limit, radial
n _{DG}	3.800 1/min	Speed on permanent grease lubrication
F _{0r per}	31.000 N	Permissible static load, radial
F _{r per}	20.600 N	Permissible dynamic load outer ring, radial
≈m	0,239 kg	Masa



Dimensions

C	24 mm	Width, outer ring
d 2	27 mm	Stop diameter of thrust washer
r min	1 mm	Minimum chamfer dimension
r 1 min	0,5 mm	Minimum chamfer dimension

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Obciążenie osiowe dwukierunkowe
- 

Smarowanie dożywotnie, bezobsługowe
- 

Smarowanie smarem
- 

Uszczelnienie dwustronne