



PWTR4090-2RS-XL

Yoke type track roller

Yoke type track rollers PWTR..-2RS-XL, double row cylindrical roller bearings with particularly thick-walled outer ring, with a central rib, full complement cylindrical roller set and an inner ring, the outer ring is guided axially by the central rib and rolling elements, protected lip seal on both sides, X-life design

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Type of Seal	2RS	Protected lip seal on both sides
Outer ring profile	IOP	Optimized INA-profile
Relubrication feature	IR	Via inner ring

Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	90 mm	Outside diameter
B	32 mm	Width of the bearing
C _{r w}	53.000 N	Basic dynamic load rating, radial
C _{0 r w}	74.000 N	Basic static load rating, radial
C _{u r w}	9.900 N	Fatigue load limit, radial
n _{D G}	1.500 1/min	Speed on permanent grease lubrication
F _{0 r per}	74.000 N	Permissible static load, radial
F _{r per}	66.000 N	Permissible dynamic load outer ring, radial
≈m	1,096 kg	Masa



Dimensions

C	30 mm	Width, outer ring
d ₂	50,5 mm	Stop diameter of thrust washer
r _{min}	1,1 mm	Minimum chamfer dimension
r _{1 min}	0,6 mm	Minimum chamfer dimension

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne