

FAG



QJ306-XL-TVP

Four-point contact bearing

Four point contact bearing QJ3...-XL-TVP, X-life, plastic cage

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	PN	Normal (ISO 492:2023)
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	30 mm	Bore diameter
D	72 mm	Outside diameter
B	19 mm	Width
C _r	61.000 N	Basic dynamic load rating, radial
C _{0r}	43.000 N	Basic static load rating, radial
C _{ur}	3.000 N	Fatigue load limit, radial
n _G	13.100 1/min	Limiting speed
n _{gr}	7.600 1/min	Reference speed
≈m	366 g	Masa

Mounting dimensions

d _{a min}	37 mm	Minimum diameter shaft shoulder
D _{a max}	65 mm	Maximum diameter of housing shoulder
r _{a max}	1 mm	Maximum fillet radius



Dimensions

r _{min}	1,1 mm	Minimum chamfer dimension
D ₁	58 mm	Shoulder diameter outer ring
d ₁	44 mm	Shoulder diameter inner ring
a	35,7 mm	Distance between the apexes of the pressure cones
α	35 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia