



FAG



QJ312-XL-MPA-C3

Four-point contact bearing

Four point contact bearing QJ3...-XL-MPA, X-life, solid brass cage

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	PN	Normal (ISO 492:2023)
Cage	MPA	Solid brass cage, outer ring guided
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Axial internal clearance	C3	Group 3 (C3), bigger than CN

Main Dimensions & Performance Data

d	60 mm	Bore diameter
D	130 mm	Outside diameter
B	31 mm	Width
C _r	152.000 N	Basic dynamic load rating, radial
C _{0r}	126.000 N	Basic static load rating, radial
C _{ur}	9.200 N	Fatigue load limit, radial
n _G	10.400 1/min	Limiting speed
n _{gr}	4.700 1/min	Reference speed
m	2,11 kg	Masa

Mounting dimensions

d _{a min}	72 mm	Minimum diameter shaft shoulder
D _{a max}	118 mm	Maximum diameter of housing shoulder
r _{a max}	2,1 mm	Maximum fillet radius



Dimensions

r_{min}	2,1 mm	Minimum chamfer dimension
D_1	106,9 mm	Shoulder diameter outer ring
d_1	84,24 mm	Shoulder diameter inner ring
a	66,5 mm	Distance between the apexes of the pressure cones
α	35 °	Contact angle

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia