



FAG

QJ313-XL-N2-MPA-C2

Four-point contact bearing

Four point contact bearing QJ3...-XL-N2-MPA,
X-life, holding grooves, solid brass cage

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design, bearing outer ring	N2	Two retaining grooves in the outer ring on one side
Tolerance class	PN	Normal (ISO 492:2023)
Cage	MPA	Solid brass cage, outer ring guided
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Axial internal clearance	C2	Group 2 (C2), smaller than CN

Main Dimensions & Performance Data

d	65 mm	Bore diameter
D	140 mm	Outside diameter
B	33 mm	Width
C _r	171.000 N	Basic dynamic load rating, radial
C _{0r}	145.000 N	Basic static load rating, radial
C _{ur}	10.800 N	Fatigue load limit, radial
n _G	9.600 1/min	Limiting speed
n _{gr}	4.450 1/min	Reference speed
≈m	2,605 kg	Masa



Mounting dimensions

$d_{a \min}$	77 mm	Minimum diameter shaft shoulder
$D_{a \max}$	128 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum fillet radius

Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
D_1	114,4 mm	Shoulder diameter outer ring
d_1	90,96 mm	Shoulder diameter inner ring
a	71,8 mm	Distance between the apexes of the pressure cones
a_n	8,1 mm	Hight retaining slot
b_n	6,5 mm	Width retaining slot
r_n	1 mm	Radius retaining slot
	45 °	Angle retaining slot
α	35 °	Contact angle

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia