


RA108-XL-NPP

Radial insert ball bearing

Radial insert ball bearings RA..-NPP, cylindrical outer ring, location by eccentric locking collar, P seals on both sides, inch size bore

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Type of Seal	NPP	Lip seal on both sides
--------------	-----	------------------------

Main Dimensions & Performance Data

d	38,1 mm	Bore diameter
d	38,1 mm	Bore diameter, inch
D	80 mm	Outside diameter
B ₁	43,7 mm	Locking collar total width
B	30,1 mm	Width
C _r	34.500 N	Basic dynamic load rating, radial
C _{0r}	19.800 N	Basic static load rating, radial
≈m	0,65 kg	Masa

Dimensions

C	21 mm	Width, outer ring
S	11 mm	Distance raceway
d ₂	49,4 mm	Rib diameter sealing inner ring
d ₃	58 mm	Outside diameter locking collar/locknut
W	4,762 mm	Width across flats (Inch)



Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne