
**RAE15-XL-NPP-FA106**

Radial insert ball bearing

Radial insert ball bearing RAE...XL-NPP

**X-life**

## Informacje techniczne

**Main Dimensions & Performance Data**

|                 |         |                                   |
|-----------------|---------|-----------------------------------|
| d               | 15 mm   | Bore diameter                     |
| D               | 40 mm   | Outside diameter                  |
| B               | 19 mm   | Width                             |
| B <sub>1</sub>  | 28,6 mm | Locking collar total width        |
| C <sub>r</sub>  | 9.800 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 4.750 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 248 N   | Fatigue load limit, radial        |
| ≈m              | 0,12 kg | Masa                              |

**Dimensions**

|                |         |                                         |
|----------------|---------|-----------------------------------------|
| C              | 12 mm   | Width, outer ring                       |
| S              | 6,5 mm  | Distance raceway                        |
| d <sub>2</sub> | 23 mm   | Rib diameter sealing inner ring         |
| d <sub>3</sub> | 28,4 mm | Outside diameter locking collar/locknut |
| W              | 3 mm    | Width of flats                          |

**Temperature range**

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -20 °C | Operating temperature min. |
| T <sub>max</sub> | 120 °C | Operating temperature max. |



Calculation factors

|                |    |                    |
|----------------|----|--------------------|
| f <sub>0</sub> | 13 | Calculation factor |
|----------------|----|--------------------|

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne