



RATR20-XL

Flanged housing unit

Housing units RATR, three-bolt flanged housing units, sheet steel, eccentric locking collar, P seals

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Material Steel sheet

Main Dimensions & Performance Data

d	20 mm	Bore diameter
H ₂	76,2 mm	Height flange
H	90 mm	Height flange
H	90,5 mm	Flange width
U	25,5 mm	Total height unit
C _r	13.600 N	Basic dynamic load rating, radial
C _{0r}	6.600 N	Basic static load rating, radial
C _{ur}	345 N	Fatigue load limit, radial
C _{0r G}	3.200 N	Load carrying capacity (housing)
C _g	3.200 N	Load carrying capacity (housing)
≈m	0,28 kg	Masa

Mounting dimensions

J	71,5 mm	Distance fixing bore
J	71,5 mm	Pitch circle diameter (holes)
N	8,7 mm	Fixing square
n	3	Number of screwing holes



Dimensions

A	8 mm	Height housing
H ₁	33,3 mm	Distance shaft axis
S	2 mm	Thickness of flange
V	55 mm	Shoulder diameter housing

Additional information

2	Number of housings
FLAN47-MSTR	Housing
RAE20-XL-NPP-B	Bearing designation

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.