



RCJHOC30-VA-FD

Flanged housing unit

Informacje techniczne

Twoja aktualna wersja produktu

Material	VA	Stainless Steel
Corrosion resistant bearing	VA	Corrosion-resistant VA design

Main Dimensions & Performance Data

d	30 mm	Bore diameter
L	108 mm	Flange width
U	54,5 mm	Total height unit
C _r	16.700 N	Basic dynamic load rating, radial
C _{0r}	9.110 N	Basic static load rating, radial
C _{ur}	760 N	Fatigue load limit, radial
≈m	1,35 kg	Masa

Mounting dimensions

J	83 mm	Distance fixing bore
N	12 mm	Fixing bore
W	3 mm	Width across flats
n	4	Number of screwing holes



Dimensions

A	45,2 mm	Height housing
A ₁	22,7 mm	Thickness of flange
A ₂	30,7 mm	Distance raceway
Y	12,7 mm	Distance housing base
d ₃	48 mm	Outside diameter locking device

Additional information

GEH.CJH06-VA-NAT	Housing
OCE30-DC-B-VA-FD	Bearing designation
KASK06-VA-G-NAT	Protecting cap

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.