



RCJHOC35-VA-FD

Flanged housing unit

Informacje techniczne

Twoja aktualna wersja produktu

Material	VA	Stainless Steel
Corrosion resistant bearing	VA	Corrosion-resistant VA design

Main Dimensions & Performance Data

d	35 mm	Bore diameter
L	117 mm	Flange width
U	58,7 mm	Total height unit
C _r	21.900 N	Basic dynamic load rating, radial
C _{0r}	12.500 N	Basic static load rating, radial
C _{ur}	1.000 N	Fatigue load limit, radial
≈m	1,68 kg	Masa

Mounting dimensions

J	92 mm	Distance fixing bore
N	14 mm	Fixing bore
W	4 mm	Width across flats
n	4	Number of screwing holes



Dimensions

A	46,7 mm	Height housing
A ₁	23,7 mm	Thickness of flange
A ₂	31,7 mm	Distance raceway
Y	12,7 mm	Distance housing base
d ₃	57 mm	Outside diameter locking device

Additional information

GEH.CJH07-VA-NAT	Housing
OCE35-DC-B-VA-FD	Bearing designation
KASK07-VA-G-NAT	Protecting cap

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.