



**RCJOC25-VA-FD**   
Flanged housing unit

Informacje techniczne

Twoja aktualna wersja produktu

|                             |    |                               |
|-----------------------------|----|-------------------------------|
| Material                    | VA | Stainless Steel               |
| Corrosion resistant bearing | VA | Corrosion-resistant VA design |

Main Dimensions & Performance Data

|                 |          |                                   |
|-----------------|----------|-----------------------------------|
| d               | 25 mm    | Bore diameter                     |
| L               | 95 mm    | Flange width                      |
| U               | 38,2 mm  | Total height unit                 |
| C <sub>r</sub>  | 12.200 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 6.500 N  | Basic static load rating, radial  |
| C <sub>ur</sub> | 550 N    | Fatigue load limit, radial        |
| ≈m              | 0,74 kg  | Masa                              |

Mounting dimensions

|   |       |                          |
|---|-------|--------------------------|
| J | 70 mm | Distance fixing bore     |
| N | 12 mm | Fixing bore              |
| W | 3 mm  | Width across flats       |
| n | 4     | Number of screwing holes |



Dimensions

|     |       |                                 |
|-----|-------|---------------------------------|
| A   | 30 mm | Height housing                  |
| A 1 | 10 mm | Thickness of flange             |
| A 2 | 16 mm | Distance raceway                |
| d 3 | 42 mm | Outside diameter locking device |

Additional information

|                  |                     |
|------------------|---------------------|
| GEH.CJ05-VA-NAT  | Housing             |
| OCE25-DC-B-VA-FD | Bearing designation |
| KASK05-VA-G-NAT  | Protecting cap      |

Temperature range

|       |        |                            |
|-------|--------|----------------------------|
| T min | -20 °C | Operating temperature min. |
| T max | 100 °C | Operating temperature max. |