

**RCJTA20-XL-N**

## Flanged housing unit

Housing units RCJTA, two-bolt flanged housing units, cast iron, adapter sleeve, R seals

**X-life**

## Informacje techniczne

## Twoja aktualna wersja produktu


|          |    |                                                   |
|----------|----|---------------------------------------------------|
| Groove   | N  | Cast iron housing with undercut slot for end caps |
| Material | GG | Grey cast iron                                    |

## Main Dimensions &amp; Performance Data

|                 |          |                                   |
|-----------------|----------|-----------------------------------|
| d               | 20 mm    | Bore diameter                     |
| L               | 61 mm    | Flange width                      |
| H               | 112 mm   | Height flange                     |
| U               | 42,5 mm  | Total height unit                 |
| C <sub>r</sub>  | 12.700 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 6.600 N  | Basic static load rating, radial  |
| C <sub>ur</sub> | 365 N    | Fatigue load limit, radial        |
| ≈m              | 0,41 kg  | Masa                              |

## Mounting dimensions

|   |         |                          |
|---|---------|--------------------------|
| J | 90 mm   | Distance fixing bore     |
| N | 11,5 mm | Fixing bore              |
| n | 2       | Number of screwing holes |





Dimensions

|                |       |                                   |
|----------------|-------|-----------------------------------|
| A              | 28 mm | Height housing                    |
| A <sub>1</sub> | 10 mm | Thickness of flange               |
| A <sub>2</sub> | 19 mm | Distance raceway                  |
| V              | 61 mm | Shoulder diameter housing         |
| Q              | M6    | Connection thread for lubrication |
| d <sub>3</sub> | 32 mm | Outside diameter locking collar   |

Additional information

|                 |                     |
|-----------------|---------------------|
| 1               | Number of housings  |
| CJT04           | Housing             |
| GSH20-XL-2RSR-B | Bearing designation |
| KASK04          | Protecting cap      |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -20 °C | Operating temperature min. |
| T <sub>max</sub> | 120 °C | Operating temperature max. |